



Наличие и актуальные цены на

**DR-30-12**

<https://www.mean-well.ru/store/DR-30-12/>



- Features :
  - \*Universal AC input/Full range
  - \*Protections: Short circuit / Overload / Over voltage
  - \*Cooling by free air convection
  - \*Can be installed on DIN rail TS-35/7.5 or 15
  - \*Isolation classII
  - \*LED indicator for power on
  - \*100% full load burn-in test
  - \*3 years warranty

User's Manual



## SPECIFICATION




| MODEL                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | DR-30-5                                                                                                                               | DR-30-12     | DR-30-15       | DR-30-24     |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------|--------------|
| OUTPUT                                  | DC VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 5V                                                                                                                                    | 12V          | 15V            | 24V          |
|                                         | RATED CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 3A                                                                                                                                    | 2A           | 2A             | 1.5A         |
|                                         | CURRENT RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0 ~ 3A                                                                                                                                | 0 ~ 2A       | 0 ~ 2A         | 0 ~ 1.5A     |
|                                         | RATED POWER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 15W                                                                                                                                   | 24W          | 30W            | 36W          |
|                                         | RIPPLE & NOISE (max.) <small>Note.2</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 80mVp-p                                                                                                                               | 120mVp-p     | 120mVp-p       | 150mVp-p     |
|                                         | VOLTAGE ADJ. RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 4.75 ~ 5.5V                                                                                                                           | 10.8 ~ 13.2V | 13.5 ~ 16.5V   | 21.6 ~ 26.4V |
|                                         | VOLTAGE TOLERANCE <small>Note.3</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | ±2.0%                                                                                                                                 | ±1.0%        | ±1.0%          | ±1.0%        |
|                                         | LINE REGULATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | ±1.0%                                                                                                                                 | ±1.0%        | ±1.0%          | ±1.0%        |
|                                         | LOAD REGULATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | ±1.0%                                                                                                                                 | ±1.0%        | ±1.0%          | ±1.0%        |
|                                         | SETUP, RISE TIME                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 100ms, 30ms/230VAC      100ms, 30ms/115VAC at full load                                                                               |              |                |              |
|                                         | HOLD UP TIME (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 100ms/230VAC      21ms/115VAC at full load                                                                                            |              |                |              |
| INPUT                                   | VOLTAGE RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 85 ~ 264VAC      120 ~ 370VDC                                                                                                         |              |                |              |
|                                         | FREQUENCY RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 47 ~ 63Hz                                                                                                                             |              |                |              |
|                                         | EFFICIENCY (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 74%                                                                                                                                   | 81%          | 82%            | 83%          |
|                                         | AC CURRENT (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 0.88A/115VAC      0.48A/230VAC                                                                                                        |              |                |              |
|                                         | INRUSH CURRENT (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | COLD START 15A/115VAC      30A/230VAC                                                                                                 |              |                |              |
| PROTECTION                              | OVERLOAD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 105 ~ 160% rated output power<br>Protection type : Constant current limiting, recovers automatically after fault condition is removed |              |                |              |
|                                         | OVER VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 5.75 ~ 6.75V                                                                                                                          | 13.8 ~ 16.2V | 17.25 ~ 20.25V | 27.6 ~ 32.4V |
|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Protection type : Shut down o/p voltage, re-power on to recover                                                                       |              |                |              |
| ENVIRONMENT                             | WORKING TEMP.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | -20 ~ +60°C (Refer to "Derating Curve")                                                                                               |              |                |              |
|                                         | WORKING HUMIDITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 20 ~ 90% RH non-condensing                                                                                                            |              |                |              |
|                                         | STORAGE TEMP., HUMIDITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | -40 ~ +85°C, 10 ~ 95% RH                                                                                                              |              |                |              |
|                                         | TEMP. COEFFICIENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | ±0.03%/°C (0 ~ 50°C)                                                                                                                  |              |                |              |
|                                         | VIBRATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes; Mounting: Compliance to IEC60068-2-6                         |              |                |              |
| SAFETY & EMC<br><small>(Note 4)</small> | SAFETY STANDARDS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | UL60950-1 approved, Design refer to EN50178                                                                                           |              |                |              |
|                                         | WITHSTAND VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | I/P-O/P:3KVAC                                                                                                                         |              |                |              |
|                                         | ISOLATION RESISTANCE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | I/P-O/P:100M Ohms / 500VDC / 25°C/ 70% RH                                                                                             |              |                |              |
|                                         | EMC EMISSION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Compliance to EN55032 (CISPR32) Class B, EN61000-3-2,-3                                                                               |              |                |              |
|                                         | EMC IMMUNITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, EN61204-3, heavy industry level, criteria A                       |              |                |              |
| OTHERS                                  | MTBF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 441.5K hrs min.      MIL-HDBK-217F (25°C)                                                                                             |              |                |              |
|                                         | DIMENSION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 78*93*56mm (W*H*D)                                                                                                                    |              |                |              |
|                                         | PACKING                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0.27Kg; 48pcs/14Kg/1.12CUFT                                                                                                           |              |                |              |
| NOTE                                    | 1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.<br>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.<br>3. Tolerance : includes set up tolerance, line regulation and load regulation.<br>4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.<br>※ Product Liability Disclaimer : For detailed information, please refer to <a href="https://www.meanwell.com/serviceDisclaimer.aspx">https://www.meanwell.com/serviceDisclaimer.aspx</a> |                                                                                                                                       |              |                |              |

## Mechanical Specification


Case No. 918B Unit:mm

Terminal Pin No. Assignment


| Pin No. | Assignment | Pin No. | Assignment |
|---------|------------|---------|------------|
| 1       | AC/N       | 5,6     | -V         |
| 2       | AC/L       | 7       | LED        |
| 3,4     | +V         | 8       | +V ADJ.    |




ADMISSIBLE DIN-RAIL: TS35/7.5 OR TS35/15



## Block Diagram



## Derating Curve



## Output Derating VS Input Voltage

