



Наличие и актуальные цены на

LDD-350H-DA

<https://www.mean-well.ru/store/LDD-350H-DA/>



■ Features :

- DC/DC step-down converter
- Constant current output: 350mA to 1400mA
- Wide input voltage: 6 ~ 50VDC
Wide output LED string voltage: 3 ~ 45VDC
- High efficiency up to 95%
- Built-in EMI filter, comply with BS EN/EN55015 without additional input filter and capacitors
- Built-in PWM and remote ON/OFF control(pin style only, wire style optional)
- Protections: Short circuit
- Cooling by free air convection
- Fully encapsulated with IP65 level
- Compact size
- Suitable for driving illumination LED
- 3 years warranty

■ GTIN CODE

MW Search: <https://www.meanwell.com/serviceGTIN.aspx>




LDD-350H-**W** DA Blank : pin style
W : wire style

SPECIFICATION

ORDER NO.		LDD-350H-□ DA	LDD-700H-□ DA	LDD-1050H-□ DA	LDD-1400H-□ DA
OUTPUT	CURRENT RANGE	350mA	700mA	1050mA	1400mA
	VOLTAGE RANGE Note.4	3 ~ 45VDC			3 ~ 36VDC
	CURRENT ACCURACY (Typ.)	±5% at 48VDC input			±5% at 28VDC input
	RIPPLE & NOISE(max.) Note.2	300mVp-p	500mVp-p	500mVp-p	500mVp-p
	SWITCHING FREQUENCY (Typ.)	500KHz			
	EXTERNAL CAPACITANCE LOAD (max.)	1400uF			
INPUT	VOLTAGE RANGE	6 ~ 50VDC			6 ~ 40VDC
	EFFICIENCY (max.)	95% at full load and 48VDC input			
	DC CURRENT	Full load Note.3	275mA	550mA	825mA
		No load	5mA		1280mA
PWM DIMMING & ON/OFF CONTROL (PIN STYLE ONLY)	FILTER	Capacitor			
	REMOTE ON/OFF	Leave open if not use			
		Power ON with dimming: DIM ~ -Vin >1.2 ~ 5VDC or open circuit, max. operation voltage 5.5VDC			
		Power OFF : DIM ~ -Vin < 0.1VDC or short			
	PWM FREQUENCY	200Hz only			
PROTECTION	QUIESCENT INPUT CURRENT IN SHUTDOWN MODE(max.)	1mA at PWM dimming OFF and 24VDC input			
	SHORT CIRCUIT	Regulated at rated output current			
		Protection type: Can be continued, recovers automatically after fault condition is removed			
ENVIRONMENT	INPUT VOLTAGE LOCKOUT	Start up	4.2VDC		
		Shut-down	3.8VDC		
	WORKING TEMP.	-40 ~ + 85℃ (Refer to derating curve)			
	WORKING HUMIDITY	20% ~ 90% RH non-condensing			
	STORAGE TEMP., HUMIDITY	-55 ~ +125℃, 10 ~ 95% RH non-condensing			
	TEMP. COEFFICIENT	±0.03% / °C			
EMC	VIBRATION	10 ~ 500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes			
	OPERATING CASE TEMP. (max.)	100℃			
	SAFETY STANDARDS	EAC TP TC 020/2011 approved			
OTHERS	EMC EMISSION	Compliance to BS EN/EN55015, EAC TP TC 020			
	EMC IMMUNITY	Compliance to BS EN/EN61547, EN61000-4-2,3,4,6,8, light industry level, criteria A, EAC TP TC 020			
	MTBF	1000Khrs min. MIL-HDBK-217F (25℃)			
NOTE	DIMENSION	40.6*23.5*10.1mm or 1.6**0.93**0.40" inch (L*W*H)			
	PACKING	LDD-H-DA: 18g ; 12pcs/per tube, 336pcs/28 tube/per carton LDD-H-WDA:23g ; 8pcs/Box, 240pcs/30 Box/per carton			
	POTTING MATERIAL	Expoxy(UL94-V0)			
NOTE		1.All parameters are specified at normal input(48VDC), rated load, 25℃ 70% RH ambient. 2.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf capacitor. 3.Test condition: 48VDC input for 350~1050mA, 28VDC input for 1400mA. 4.Output voltage will always step down by 3 volts from input DC voltage. 5.The output of LDD-H should not be connected to the input of the same unit or output from other sources. ※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx			


Mechanical Specification

Pin style(LDD- 350H~1400H – DA):



NOTE: Pin tolerance $\pm 0.05\text{mm}$

Wire style(LDD – 350H~1400H-WDA):




NOTE: Wire is 24AWG

Pin Configuration



Pin No.		Comment
2	+Vin	DC supply
4	+Vout	LED+ connection
6	-Vout	LED- connection
7	DA	Connect to DALI Controller
8	DA	
14	PWM DIM	PWM Dimming
15	-Vin	DC supply, Don't connect to -Vout

Pin No.		Comment
2	+Vin (Red)	DC supply
4	+Vout (Yellow)	LED+ connection
6	-Vout (Blue)	LED- connection
7	DA (Brown)	Connect to DALI Controller
8	DA (Brown)	
15	-Vin (Black)	DC supply, Don't connect to -Vout

■ PWM Dimming Control & Diagram(pin style only, wire style optional)



⊙ During PWM dimming operation, the output current will change to PWM style.



■ Efficiency VS Output Voltage(Number of LEDs)

Fig-1 12VDC input, 1~3 LEDs(Vf=3V)




Fig-2 24VDC input, 1~7 LEDs(Vf=3V)




Fig-3 36VDC input, 1~11 LEDs(Vf=3V)








Fig-4 48VDC input, 1~15 LEDs(Vf=3V)




■ Derating Curve



Packing

Standard Tube Packing	LDD-H-DA			
	MPQ Per Tube (PCS)	One Tube G.W.	Max. Q'TY/ Carton(PCS)	One Carton G.W.
Unit : mm  Tube Nails Product Foam 535 26.5 10.9 Tube pattern  CARTON L590.9 x W148.5 x H193.9	12	308g	336	10.63Kg

Standard Packing	LDD-H-WDA			
	MPQ Per Box (PCS)	One Box G.W.	Max. Q'TY/ Carton(PCS)	One Carton G.W.
Unit : mm  CARTON L421.2 x W357.5 x H284.8	8	205g	240	8.15Kg

■ Installation Manual

Please refer to : <http://www.meanwell.com/manual.html>