



Наличие и актуальные цены на

SE-1500-48

<https://www.mean-well.ru/store/SE-1500-48/>



- Features :
- AC input 180 ~ 264VAC
 - AC input active surge current limiting
 - Protections: Short circuit / Overload / Over voltage / Over temperature
 - Forced air cooling by built-in DC ball bearing fan
 - High power density 7.8w/inch³
 - With DC OK signal output
 - Built-in remote ON-OFF control
 - Built-in remote sense function
 - UL / CUL approved
 - Low cost
 - 2 years warranty



■ GTIN CODE


MW Search: <https://www.meanwell.com/serviceGTIN.aspx>



SPECIFICATION

MODEL		SE-1500-5		SE-1500-12		SE-1500-15		SE-1500-24		SE-1500-27		SE-1500-48	
OUTPUT	DC VOLTAGE	5V		12V		15V		24V		27V		48V	
	RATED CURRENT	300A		125A		100A		62.5A		55.6A		31.3A	
	CURRENT RANGE	0 ~ 300A		0 ~ 125A		0 ~ 100A		0 ~ 62.5A		0 ~ 55.6A		0 ~ 31.3A	
	RATED POWER	1500W		1500W		1500W		1500W		1501.2W		1502.4W	
	RIPPLE & NOISE (max.) Note.2	150mVp-p		150mVp-p		150mVp-p		150mVp-p		150mVp-p		150mVp-p	
	VOLTAGE ADJ. RANGE	3.3 ~ 5.5V		10.8 ~ 13.5V		13.5 ~ 16.5V		21.6 ~ 26.4V		25 ~ 30V		43.2 ~ 56V	
	VOLTAGE TOLERANCE Note.3	± 2.0%		± 1.0%		± 1.0%		± 1.0%		± 1.0%		± 1.0%	
	LINE REGULATION	± 0.5%		± 0.5%		± 0.5%		± 0.5%		± 0.5%		± 0.5%	
	LOAD REGULATION	± 2.0%		± 0.5%		± 0.5%		± 0.5%		± 0.5%		± 0.5%	
	SETUP, RISE TIME	150ms, 12ms / 230VAC at full load											
	HOLD UP TIME (Typ.)	26ms / 230VAC at full load											
INPUT	VOLTAGE RANGE	180 ~ 264VAC		254 ~ 370VDC									
	FREQUENCY RANGE	47 ~ 63Hz											
	EFFICIENCY (Typ.)	81%		85%		85%		87%		88%		89%	
	AC CURRENT (Typ.)	17.5A / 230VAC											
	INRUSH CURRENT (Typ.)	60A / 230VAC											
	LEAKAGE CURRENT	<3.5mA / 240VAC											
PROTECTION	OVERLOAD	105 ~ 125% rated output power Protection type : Shut down o/p voltage, re-power on to recover											
	OVER VOLTAGE	5.75 ~ 6.75V		14.5 ~ 16.2V		18 ~ 21V		27.6 ~ 32.4V		31 ~ 35V		57.6 ~ 67.2V	
		Protection type : Shut down o/p voltage, re-power on to recover											
	OVER TEMPERATURE	Shut down o/p voltage, recovers automatically after temperature goes down											
FUNCTION	DC_OK SIGNAL	PSU turn on:3.3V ~ 5.6V PUS turn off:0 ~ 1V											
	REMOTE CONTROL	RC+/RC-: 0 ~ 0.8V power on; 4 ~ 10V power off											
ENVIRONMENT	WORKING TEMP.	-20 ~ +70℃ (Refer to "Derating Curve")											
	WORKING HUMIDITY	20 ~ 90% RH non-condensing											
	STORAGE TEMP., HUMIDITY	-40 ~ +85℃, 10 ~ 95% RH											
	TEMP. COEFFICIENT	± 0.05%/℃ (0 ~ 50℃)											
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes											
SAFETY & EMC (Note 4)	SAFETY STANDARDS	UL62368-1, BSMI CNS15598-1, EAC TP TC 004 approved; Design refer to BS EN/EN62368-1											
	WITHSTAND VOLTAGE	I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC											
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25℃ / 70% RH											
	EMC EMISSION	Parameter	Standard					Test Level / Note					
		Conducted	BS EN/EN55032 (CISPR32),CNS15936					Class A					
		Radiated	BS EN/EN55032 (CISPR32),CNS15936					Class A					
		Harmonic Current	BS EN/EN61000-3-2					-----					
		Voltage Flicker	BS EN/EN61000-3-3					-----					
	EMC IMMUNITY	BS EN/EN55035, BS EN/EN61000-6-2											
		Parameter	Standard					Test Level / Note					
ESD		BS EN/EN61000-4-2					Level 3, 8KV air ; Level 2, 4KV contact						
Radiated		BS EN/EN61000-4-3					Level 3						
EFT / Burst		BS EN/EN61000-4-4					Level 3						
Surge		BS EN/EN61000-6-2					2KV/Line-Line 4KV/Line-Earth						
Conducted		BS EN/EN61000-4-6					Level 3						
Magnetic Field		BS EN/EN61000-4-8					Level 4						
Voltage Dips and Interruptions		BS EN/EN61000-4-11					>95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods						
OTHERS	MTBF	999.9K hrs min. Telcordia SR-332 (Bellcore) ; 134.5K hrs min. MIL-HDBK-217F (25℃)											
	DIMENSION	278*177.8*63.5mm (L*W*H)											
	PACKING	3.3Kg; 4pcs/14.2Kg/1.14CUFT											

Mechanical Specification




Terminal Pin No. Assignment :

Pin No.	Assignment
1	AC/L
2	AC/N
3	FG $\perp$


Control Pin (CN3) : JST B6B-XH or equivalent

Pin No.	Assignment	Pin No.	Assignment	Mating Housing	Terminal
1	DC_OK Signal	4	+S	JST XHP or equivalent	JST SXH-001T or equivalent
2	DC_OK GND	5	RC-		
3	-S	6	RC+		


Block Diagram



Derating Curve



Static Characteristics



Function Description of CN3


Pin No.	Function	Description
1	DC_OK	DC_OK signal is a TTL level signal, referenced to pin2(DC_OK GND). "High" when PSU turns on.
2	GND	This pin connects to the negative terminal (-V). Return for DC_OK signal output.
3	-S	Negative sensing. The -S signal should be connected to the negative terminal of the load. The -S and +S leads should be twisted in pair to minimize noise pick-up effect.
4	+S	Positive sensing. The +S signal should be connected to the positive terminal of the load. The +S and -S leads should be twisted in pair to minimize noise pick-up effect.
5	RC-	Return for RC+ signal input.
6	RC+	Turns the output on and off by electrical or dry contact between pin 6 (RC+) and pin 5 (RC-). 0~0.8V: Power ON, 4~10V: Power OFF.

Function Manual

1.DC_OK Signal

DC_OK Signal is a TTL level signal. "High" when PSU turns on.


Between DC_OK(pin1) and GND(pin2)	Output Status
3.3 ~ 5.6V	ON
0 ~ 1V	OFF



2. Remote Control

The PSU can be turned ON/OFF by using the "Remote Control" function.

Between RC+(pin6) and RC-(pin5)	Output Status
SW OFF (0 ~ 0.8V)	ON
SW ON (4 ~ 10V)	OFF



3. Remote Sense

