




Наличие и актуальные цены на

**SPB03C-12**

<https://www.mean-well.ru/store/SPB03C-12/>



■ Features :


- 2:1 wide input range
- 1000VDC I/O isolation
- Built-in remote ON/OFF control
- Built-in EMI filter
- Protections: Short circuit / Overload
- Cooling by free air convection
- Single in line package
- 100% full load burn-in test
- Low cost / High reliability
- Modified models available: output 3.3V/9V
- 2 years warranty



## SPECIFICATION

| ORDER NO.                              |                                             | SPB03E-05                                                                                                  | SPB03A-05                                | SPB03B-05 | SPB03C-05 | SPB03E-12  | SPB03A-12 | SPB03B-12 | SPB03C-12 | SPB03E-15  | SPB03A-15 | SPB03B-15 | SPB03C-15 |  |
|----------------------------------------|---------------------------------------------|------------------------------------------------------------------------------------------------------------|------------------------------------------|-----------|-----------|------------|-----------|-----------|-----------|------------|-----------|-----------|-----------|--|
| OUTPUT                                 | DC VOLTAGE                                  | 5V                                                                                                         |                                          |           |           | 12V        |           |           |           | 15V        |           |           |           |  |
|                                        | CURRENT RANGE                               | 60 ~ 600mA                                                                                                 |                                          |           |           | 25 ~ 250mA |           |           |           | 20 ~ 200mA |           |           |           |  |
|                                        | RATED POWER                                 | 3W                                                                                                         |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | RIPPLE & NOISE (max.) <small>Note.2</small> | 50mVp-p                                                                                                    |                                          |           |           | 60mVp-p    |           |           |           | 60mVp-p    |           |           |           |  |
|                                        | LINE REGULATION <small>Note.3</small>       | ±0.5%                                                                                                      |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | LOAD REGULATION <small>Note.4</small>       | ±0.5%                                                                                                      |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | VOLTAGE ACCURACY                            | ±2.0%                                                                                                      |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | SWITCHING FREQUENCY                         | 100KHz min.                                                                                                |                                          |           |           |            |           |           |           |            |           |           |           |  |
| INPUT                                  | VOLTAGE RANGE                               | E: 4.5 ~ 9VDC   A: 9 ~ 18VDC   B: 18 ~ 36VDC   C: 36 ~ 72VDC                                               |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | EFFICIENCY (Typ.)                           | 74%                                                                                                        | 73%                                      | 77%       | 78%       | 76%        | 80%       | 80%       | 79%       | 75%        | 80%       | 80%       | 82%       |  |
|                                        | DC CURRENT                                  | Full load                                                                                                  | E: 810mA   A: 340mA   B: 165mA   C: 85mA |           |           |            |           |           |           |            |           |           |           |  |
|                                        |                                             | No load                                                                                                    | E: 110mA   A: 40mA   B: 20mA   C: 10mA   |           |           |            |           |           |           |            |           |           |           |  |
|                                        | FILTER                                      | Capacitor Type                                                                                             |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | REMOTE CONTROL                              | Power ON : R.C. ~ -Vin < 1VDC or open ; Power OFF : R.C. ~ -Vin > 4VDC                                     |                                          |           |           |            |           |           |           |            |           |           |           |  |
| PROTECTION                             | Fuse recommended                            |                                                                                                            |                                          |           |           |            |           |           |           |            |           |           |           |  |
| PROTECTION<br><small>(Note. 5)</small> | OVERLOAD                                    | 150 ~ 250% rated output power<br>Protection type : Recovers automatically after fault condition is removed |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | SHORT CIRCUIT                               | All output equipped with short circuit                                                                     |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        |                                             | Protection type : Recovers automatically after fault condition is removed                                  |                                          |           |           |            |           |           |           |            |           |           |           |  |
| ENVIRONMENT                            | WORKING TEMP.                               | -40 ~ +85℃ (Refer to "Derating Curve")                                                                     |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | WORKING HUMIDITY                            | 20% ~ 90% RH non-condensing                                                                                |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | STORAGE TEMP., HUMIDITY                     | -40 ~ +105℃, 10 ~ 95% RH                                                                                   |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | TEMP. COEFFICIENT                           | ±0.05% / °C (0 ~ 50℃)                                                                                      |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | VIBRATION                                   | 10 ~ 500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes                                   |                                          |           |           |            |           |           |           |            |           |           |           |  |
| SAFETY                                 | SAFETY STANDARDS                            | EAC TP TC 004 approved                                                                                     |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | WITHSTAND VOLTAGE                           | I/P-O/P:1KVDC                                                                                              |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | ISOLATION RESISTANCE                        | I/P-O/P: 100M Ohms / 500VDC / 25℃ / 70% RH                                                                 |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | ISOLATION CAPACITANCE                       | 80pF max.                                                                                                  |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | EMC EMISSION                                | Compliance to EN55032 Class B, FCC part 15 Class B, EAC TP TC 020                                          |                                          |           |           |            |           |           |           |            |           |           |           |  |
| OTHERS                                 | EMC IMMUNITY                                | Compliance to EN61000-4-2,3,4,5,6,8 light industry level, criteria A, EAC TP TC 020                        |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | MTBF                                        | 600Khrs min. MIL-HDBK-217F(25℃)                                                                            |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | DIMENSION                                   | 21.8*9.2*11.1mm or 0.86**0.36**0.44" inch (L*W*H)                                                          |                                          |           |           |            |           |           |           |            |           |           |           |  |
|                                        | WEIGHT                                      | 4.8g                                                                                                       |                                          |           |           |            |           |           |           |            |           |           |           |  |


## ■ Mechanical Specification



## ■ Pin Configuration

| Pin No. | Output |
|---------|--------|
| 1       | -Vin   |
| 2       | +Vin   |
| 3       | R.C.   |
| 5       | N.C.   |
| 6       | +Vout  |
| 7       | -Vout  |
| 8       | N.C.   |

### Derating Curve



**NOTE**

- 1.All parameters are specified at normal input, rated load, 25°C 70% RH ambient.
  - 2.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
  - 3.Line regulation is measured from low line to high line at rated load.
  - 4.Load regulation is measured from 10% to 100% rated load.
  - 5.Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.
- ※ Product Liability Disclaimer : For detailed information, please refer to <https://www.meanwell.com/serviceDisclaimer.aspx>